



## PE 100 Stub flanges for loose flange ISO/DIN, injected

d	d3	d4	e	h1	h4	z1	kg/piece	SDR	Article number
mm	mm	mm	mm	mm	mm	mm	kg	SDR	
32	40.0	68	3.0	10	62	86	0.1	11	<a href="#">19400105</a>
40	50.0	78	3.7	11	62	89	0.1	11	<a href="#">19400106</a>
50	60.0	88	4.6	12	62	90	0.1	11	<a href="#">19400108</a>
63	75.0	102	5.8	14	70	106	0.2	11	<a href="#">19400034</a>
75	89.0	122	6.8	16	94	129	0.3	11	<a href="#">19400035</a>
90	105.0	138	8.2	17	100	140	0.5	11	<a href="#">19400037</a>
110	125.0	158	10.0	18	113	160	0.7	11	<a href="#">19400039</a>
125	132.0	158	11.4	25	134	183	0.9	11	<a href="#">19400041</a>
140	155.0	188	12.7	25	128	182	1.3	11	<a href="#">19400111</a>
160	175.0	212	14.6	25	155	208	1.6	11	<a href="#">19400043</a>
180		212	16.4	30	168	202	2.0	11	<a href="#">19400046</a>
200	232.0	268	18.2	32	128	200	3.1	11	<a href="#">19400112</a>
225	235.0	268	20.5	32	135	201	3.3	11	<a href="#">19400050</a>
250	285.0	320	22.7	35	138	219	4.9	11	<a href="#">19400129</a>
280	291.0	320	25.4	35	152	231	5.6	11	<a href="#">19400132</a>
315	335.0	370	28.6	35	158	239	7.8	11	<a href="#">19400134</a>
355	373.0	430	32.2	40	176	260	10.4	11	<a href="#">19400192</a>
400	427.0	482	36.3	46	195	290	14.6	11	<a href="#">19400194</a>
50	60.0	88	3.0	12	62	90	0.1	17	<a href="#">19400107</a>
63	75.0	102	3.8	14	70	106	0.2	17	<a href="#">19400119</a>
75	89.0	122	4.5	16	92	130	0.3	17	<a href="#">19400109</a>
90	105.0	138	5.4	17	100	140	0.4	17	<a href="#">19400121</a>
110	125.0	158	6.6	18	113	158	0.5	17	<a href="#">19400122</a>
125	132.0	158	7.4	18	141	183	0.6	17	<a href="#">19400123</a>
140	153.0	188	8.3	18	130	173	1.2	17	<a href="#">19400110</a>
160	175.0	212	9.5	18	160	208	1.3	17	<a href="#">19400042</a>
180		212	10.7	20	175	175	2.2	17	<a href="#">19400045</a>
200	232.0	268	11.9	24	133	199	2.2	17	<a href="#">19400126</a>
225	235.0	268	13.4	24	135	201	3.5	17	<a href="#">19400049</a>
250	285.0	320	14.8	25	148	220	4.0	17	<a href="#">19400128</a>
280	291.0	320	16.6	25	154	230	4.8	17	<a href="#">19400131</a>
315	335.0	370	18.7	25	166	242	5.1	17	<a href="#">19400133</a>
355	373.0	430	21.1	30	179	261	7.3	17	<a href="#">19400191</a>
400	427.0	482	23.7	33	195	290	10.3	17	<a href="#">19400193</a>